



AIR HOSE

Tube: black, smooth, synthetic rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover: black or red, smooth (wrapped finish) synthetic rubber, abrasion, weather and abrasion resistant

Application:for a variety of general purposes in industries, construction sites and mines.

Temp Range: -35℃ to 80℃

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~2.0	145~290	3.0~6.0	430~870	0.13	100±1%
6	1/4"	13	1.0~2.0	145~290	3.0~6.0	430~870	0.15	100±1%
8	5/16"	15	1.0~2.0	145~290	3.0~6.0	430~870	0.23	100±1%
10	3/8"	17	1.0~2.0	145~290	3.0~6.0	430~870	0.26	100±1%
13	1/2"	22	1.0~2.0	145~290	3.0~6.0	430~870	0.36	100±1%
16	5/8"	25	1.0~2.0	145~290	3.0~6.0	430~870	0.53	100±1%
19	3/4"	29	1.0~2.0	145~290	3.0~6.0	430~870	0.64	100±1%
25	1"	36	1.0~2.0	145~290	3.0~6.0	430~870	0.85	100±1%
32	1.1/4"	43	1.0~2.0	145~290	3.0~6.0	430~870	1.2	50±1%
38	1.1/2"	50	1.0~2.0	145~290	3.0~6.0	430~870	1.39	50±1%
51	2"	65	1.0~2.0	145~290	3.0~6.0	430~870	1.8	50±1%



WATER HOSE

Tube: black, smooth, synthetic rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover: black or green, smooth (wrapped finish) synthetic rubber, abrasion, weather and abrasion resistant

Application:for a variety of general purposes in industries, construction sites and mines.

Temp Range:-35℃ to 80℃"

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	0.3~1.0	45~145	0.9~3.0	130~430	0.13	100±1%
6	1/4"	13	0.3~1.0	45~145	0.9~3.0	130~430	0.15	100±1%
8	5/16"	15	0.3~1.0	45~145	0.9~3.0	130~430	0.23	100±1%
10	3/8"	17	0.3~1.0	45~145	0.9~3.0	130~430	0.26	100±1%
13	1/2"	22	0.3~1.0	45~145	0.9~3.0	130~430	0.36	100±1%
16	5/8"	25	0.3~1.0	45~145	0.9~3.0	130~430	0.53	100±1%
19	3/4"	29	0.3~1.0	45~145	0.9~3.0	130~430	0.64	100±1%
25	1"	36	0.3~1.0	45~145	0.9~3.0	130~430	0.85	100±1%
32	1.1/4"	43	0.3~1.0	45~145	0.9~3.0	130~430	1.2	50±1%
38	1.1/2"	50	0.3~1.0	45~145	0.9~3.0	130~430	1.39	50±1%
51	2"	65	0.3~1.0	45~145	0.9~3.0	130~430	1.8	50±1%



FULE OIL HOSE

Tube: black, smooth, nitrile rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover:black, smooth (wrapped finish) synthetic rubber, abrasion, weather and oil mist resistant

Application:use on hydraulic systems such as oil return hose,can also be used for various petroleum products

Temp Range:-40℃ to 100℃

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	0.3~1.0	45~145	0.9~3.0	130~430	0.13	100±1%
6	1/4"	13	0.3~1.0	45~145	0.9~3.0	130~430	0.15	100±1%
8	5/16"	15	0.3~1.0	45~145	0.9~3.0	130~430	0.23	100±1%
10	3/8"	17	0.3~1.0	45~145	0.9~3.0	130~430	0.26	100±1%
13	1/2"	22	0.3~1.0	45~145	0.9~3.0	130~430	0.36	100±1%
16	5/8"	25	0.3~1.0	45~145	0.9~3.0	130~430	0.53	100±1%
19	3/4"	29	0.3~1.0	45~145	0.9~3.0	130~430	0.64	100±1%
25	1"	36	0.3~1.0	45~145	0.9~3.0	130~430	0.85	100±1%
32	1.1/4"	43	0.3~1.0	45~145	0.9~3.0	130~430	1.2	50±1%
38	1.1/2"	50	0.3~1.0	45~145	0.9~3.0	130~430	1.39	50±1%
51	2"	65	0.3~1.0	45~145	0.9~3.0	130~430	1.8	50±1%



OXYGEN HOSE

Tube: black, smooth, synthetic rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Application: for conveying welding gases.

Cover: blue or black smooth(streaky finish) synthetic rubber, abrasion, weather and abrasion resistant

Temp Range: -35℃ to 90℃

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~2.0	145~290	3.0~6.0	430~870	0.13	100±1%
6	1/4"	13	1.0~2.0	145~290	3.0~6.0	430~870	0.15	100±1%
8	5/16"	15	1.0~2.0	145~290	3.0~6.0	430~870	0.23	100±1%
10	3/8"	17	1.0~2.0	145~290	3.0~6.0	430~870	0.26	100±1%
13	1/2"	22	1.0~2.0	145~290	3.0~6.0	430~870	0.36	100±1%
16	5/8"	25	1.0~2.0	145~290	3.0~6.0	430~870	0.53	100±1%
19	3/4"	29	1.0~2.0	145~290	3.0~6.0	430~870	0.64	100±1%
25	1"	36	1.0~2.0	145~290	3.0~6.0	430~870	0.85	100±1%



ACETYLENE HOSE

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~2.0	145~290	3.0~6.0	430~870	0.13	100±1%
6	1/4"	13	1.0~2.0	145~290	3.0~6.0	430~870	0.15	100±1%
8	5/16"	15	1.0~2.0	145~290	3.0~6.0	430~870	0.23	100±1%
10	3/8"	17	1.0~2.0	145~290	3.0~6.0	430~870	0.26	100±1%
13	1/2"	22	1.0~2.0	145~290	3.0~6.0	430~870	0.36	100±1%
16	5/8"	25	1.0~2.0	145~290	3.0~6.0	430~870	0.53	100±1%
19	3/4"	29	1.0~2.0	145~290	3.0~6.0	430~870	0.64	100±1%



TWIN WELDING HOSE

Tube: black, smooth, synthetic rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover: blue and red, smooth synthetic rubber, abrasion, weather and abrasion resistant

Application: for conveying welding gases.

Temp Range: -35℃ to 90℃

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~2.0	145~290	3.0~6.0	430~870	0.13	100±1%
6	1/4"	13	1.0~2.0	145~290	3.0~6.0	430~870	0.15	100±1%
8	5/16"	15	1.0~2.0	145~290	3.0~6.0	430~870	0.23	100±1%
10	3/8"	17	1.0~2.0	145~290	3.0~6.0	430~870	0.26	100±1%
13	1/2"	22	1.0~2.0	145~290	3.0~6.0	430~870	0.36	100±1%



LPG HOSE

Tube: black, smooth, nitrile rubber

Reinforcement: high tensile synthetic yarn braided or spiraled

Cover: orange,smooth (wrapped finish) synthetic rubber, abrasion, weather and oil mist resistant

Application: for conveyance of liquid gas, home burner system, grill, oil-resistant

Temperature: -40℃ to~+90℃

I.D.		O.D.	W.P.		B.P.		WEIGHT	LENGTH MAX.
MM	INCH	MM	MPA	PSI	MPA	PSI	KG/M	M/ROLL
5	3/16"	12	1.0~2.0	145~290	3.0~6.0	430~870	0.13	100±1%
6	1/4"	13	1.0~2.0	145~290	3.0~6.0	430~870	0.15	100±1%
8	5/16"	15	1.0~2.0	145~290	3.0~6.0	430~870	0.23	100±1%
10	3/8"	17	1.0~2.0	145~290	3.0~6.0	430~870	0.26	100±1%
13	1/2"	22	1.0~2.0	145~290	3.0~6.0	430~870	0.36	100±1%

I.D.		Ply.	W.P.	B.P.	LENGTH
MM	INCH		MPA	MPA	M/ROLL
13	1/2"	2~3	0.5~1.0	2.0~4.0	20
16	5/8"	3~4	0.5~1.0	2.0~4.0	20
19	3/4"	3~7	0.5~1.0	2.0~4.0	20
25	1"	4~7	0.5~1.0	2.0~4.0	20
32	1.1/4"	4~7	0.5~1.0	2.0~4.0	20
38	1.1/2"	4~8	0.5~1.0	2.0~4.0	20
51	2"	5~10	0.5~1.0	2.0~4.0	20
64	2.1/2"	5~10	0.5~1.0	2.0~4.0	20
76	3"	5~10	0.5~1.0	2.0~4.0	20
89	3.1/2"	5~12	0.5~1.0	2.0~4.0	20
102	4"	5~12	0.5~1.0	2.0~4.0	20
127	5"	5~12	0.5~1.0	2.0~4.0	20
150	6"	5~12	0.5~1.0	2.0~4.0	20



FABRIC REINFORCED AIR HOSE

Applications:For delivery of compressed air or inert gases in faltories.mines and construction work,etc.It may be used to connect the pneumatic tools.pneumatic machines and so on.

Features:Made of excellent air impervious rubber.
Factor of safety: 4

I.D.		Ply.	W.P.	B.P.	LENGTH
MM	INCH		MPA	MPA	M/ROLL
13	1/2"	1~3	0.3~1.0	0.9~3.0	20
16	5/8"	2~4	0.3~1.0	0.9~3.0	20
19	3/4"	2~7	0.3~1.0	0.9~3.0	20
25	1"	2~7	0.3~1.0	0.9~3.0	20
32	1.1/4"	3~7	0.3~1.0	0.9~3.0	20
38	1.1/2"	3~8	0.3~1.0	0.9~3.0	20
51	2"	4~10	0.3~1.0	0.9~3.0	20
64	2.1/2"	4~10	0.3~1.0	0.9~3.0	20
76	3"	4~10	0.3~1.0	0.9~3.0	20
89	3.1/2"	4~12	0.3~1.0	0.9~3.0	20
102	4"	4~12	0.3~1.0	0.9~3.0	20
127	5"	4~12	0.3~1.0	0.9~3.0	20
150	6"	4~12	0.3~1.0	0.9~3.0	20



FABRIC REINFORCED WATER HOSE

Applications:For delivery of water and other neutral liquids at normal temperature in industry,mining,agriculture,construction work,parks and at home.

Feature:It is excelent in flexibility and aging resistance as well as light in weight.
Factor of safety:3

I.D.		Ply.	W.P.	B.P.	LENGTH
MM	INCH		MPA	MPA	
13	1/2"	2~3	0.5~1.0	2.0~4.0	20
16	5/8"	3~4	0.5~1.0	2.0~4.0	20
19	3/4"	3~7	0.5~1.0	2.0~4.0	20
25	1"	4~7	0.5~1.0	2.0~4.0	20
32	1.1/4"	4~7	0.5~1.0	2.0~4.0	20
38	1.1/2"	4~8	0.5~1.0	2.0~4.0	20
51	2"	5~10	0.5~1.0	2.0~4.0	20
64	2.1/2"	5~10	0.5~1.0	2.0~4.0	20
76	3"	5~10	0.5~1.0	2.0~4.0	20
89	3.1/2"	5~12	0.5~1.0	2.0~4.0	20
102	4"	5~12	0.5~1.0	2.0~4.0	20
127	5"	5~12	0.5~1.0	2.0~4.0	20
150	6"	5~12	0.5~1.0	2.0~4.0	20



FABRIC REINFORCED OIL HOSE

Applications:For delivery of gasoline,kerosene, diesel oil and other mineral oils at room temperature in factory.Mining oil depot,oil jetty,etc.

Features:It is made of special syntheic rubber possessing excellent oil-resistant character.

Factor of safety:4

I.D.		Ply.	W.P.	B.P.	LENGTH
MM	INCH		MPA	MPA	
13	1/2"	1~3	0.3~1.0	0.9~3.0	20
16	5/8"	2~4	0.3~1.0	0.9~3.0	20
19	3/4"	2~7	0.3~1.0	0.9~3.0	20
25	1"	2~7	0.3~1.0	0.9~3.0	20
32	1.1/4"	3~7	0.3~1.0	0.9~3.0	20
38	1.1/2"	3~8	0.3~1.0	0.9~3.0	20
51	2"	4~10	0.3~1.0	0.9~3.0	20
64	2.1/2"	4~10	0.3~1.0	0.9~3.0	20
76	3"	4~10	0.3~1.0	0.9~3.0	20
89	3.1/2"	4~12	0.3~1.0	0.9~3.0	20
102	4"	4~12	0.3~1.0	0.9~3.0	20
127	5"	4~12	0.3~1.0	0.9~3.0	20
150	6"	4~12	0.3~1.0	0.9~3.0	20




FABRIC REINFORCED HOT WATER HOSE

Applications:For intermittent conveying saturated vapour or superheated water at a temperature below 100℃.

Features:Made of excellent heat resistan rubber and materials.It is safe for use.

Factor of safety:3

I.D.		Ply.	W.P.	B.P.	LENGTH
MM	INCH		MPA	MPA	M/ROLL
16	5/8"	4~7	0.5~1.0	2.5~5.0	20
19	3/4"	4~7	0.5~1.0	2.5~5.0	20
25	1"	5~7	0.5~1.0	2.5~5.0	20
32	1.1/4"	5~7	0.5~1.0	2.5~5.0	20
38	1.1/2"	5~8	0.5~1.0	2.5~5.0	20
51	2"	6~10	0.5~1.0	2.5~5.0	20
64	2.1/2"	6~10	0.5~1.0	2.5~5.0	20
76	3"	6~10	0.5~1.0	2.5~5.0	20
89	3.1/2"	6~12	0.5~1.0	2.5~5.0	20
102	4"	6~12	0.5~1.0	2.5~5.0	20
127	5"	6~12	0.5~1.0	2.5~5.0	20
150	6"	6~12	0.5~1.0	2.5~5.0	20



FABRIC REINFORCED STEAM HOSE

Applications:For intermittent conveying saturated vapour or superheated water at a temperature below 175°C. The vapour pressure above 0.4 MPa is not allowed.

Features:Made of excellent heat resistan rubber and materials.It is safe for use.

Factor of safety:5.

I.D.		Ply.	W.P.	B.P.	LENGTH
MM	INCH		MPA	MPA	M/ROLL
13	1/2"	2~3	0.5~1.0	2.0~4.0	20
16	5/8"	3~4	0.5~1.0	2.0~4.0	20
19	3/4"	3~7	0.5~1.0	2.0~4.0	20
25	1"	4~7	0.5~1.0	2.0~4.0	20
32	1.1/4"	4~7	0.5~1.0	2.0~4.0	20
38	1.1/2"	4~8	0.5~1.0	2.0~4.0	20
51	2"	5~10	0.5~1.0	2.0~4.0	20
64	2.1/2"	5~10	0.5~1.0	2.0~4.0	20
76	3"	5~10	0.5~1.0	2.0~4.0	20
89	3.1/2"	5~12	0.5~1.0	2.0~4.0	20
102	4"	5~12	0.5~1.0	2.0~4.0	20
127	5"	5~12	0.5~1.0	2.0~4.0	20
150	6"	5~12	0.5~1.0	2.0~4.0	20



FABRIC REINFORCED ACID-ALKALI HOSE

Applications:For conveying sulphuric acid with a concentration below 40% and other inorganic acids (except nitric acid)as well as dilute alk alkaline solutions at room temperature.

Features:Made of excellent chemical corrosion resistant rubber and other special materials, possessing good acid-alkali resistance.

Factor of safety:4.

I.D.		Ply.	W.P.	B.P.	LENGTH
MM	INCH		MPA	MPA	M/ROLL
16	5/8"	29	1	3	60
19	3/4"	35	1	3	60
25	1"	39	1	3	60
32	1.1/4"	49	1	3	60
38	1.1/2"	55	1	3	60
38	1.1/2"	60	1	3	60
51	2"	71	1	3	60
64	2.1/2"	85	1	3	60
76	3"	97	1	3	60
89	3.1/2"	103	1	3	60
102	4"	129	1	3	40



SAND BLASTE HOSE

Applications:For sand-biasting and eliminating rust on the surface of metal parts.

Features:The inner tube is made of excellent wear-resistant rubber,possessing good pressure resistance.

Factor of safety:4



SUCTION AND DISCHARGE WATER HOSE

Tube: black, smooth, compounded for long wear resistance in handling hard, sharp abrasive materials such as sand, gravel, shells, stones, etc.

Reinforcement: high strength synthetic cord plus helix wire

Cover:black, corrugated (wrapped finish) synthetic rubber highly resistant to weather, sea-water and abrasion

Application:Dry material suction and delivery hose specially designed for transfer of dry cement, sand gravel, feed, seeds, etc. by suction, gravity or by pneumatic systems.

Temp Range: -40°C to 85°C

I.D		O.D	W.P.	B.P.	WEIGHT	LENGTH MAX.
MM	INCHI	MM	MPA	MPA	KG/M	M/ROLL
51	2"	63	10	30	1.72	60
64	2.1/2"	77	10	30	2.37	60
76	3"	91	10	30	3.86	60
102	4"	120	10	30	4.33	60
127	5"	148	10	30	7.23	60
152	6"	175	10	30	10.18	40



SUCTION AND DISCHARGE OIL HOSE

Tube: black, smooth, nitrile rubber compound

Reinforcement: high strength synthetic cord plus helix wire.

Cover:black, smooth (wrapped finish) high grade chloroprene rubber, compounded for an excellent resistance to weather, ozone, abrasion and oil.

Application:used for delivery and transfer of a wide range of petroleum products.

Temp Range: -40°C to 100°C

I.D		O.D	W.P.	B.P.	WEIGHT	LENGTH MAX.
MM	INCHI	MM	MPA	MPA	KG/M	M/ROLL
51	2"	61	0.3~1.0	0.9~3.0	1.4	60
64	2.1/2"	74	0.3~1.0	0.9~3.0	1.8	60
76	3"	87	0.3~1.0	0.9~3.0	2.1	60
90	3.1/2"	102	0.3~1.0	0.9~3.0	3	60
102	4"	115	0.3~1.0	0.9~3.0	3.7	60
127	5"	141	0.3~1.0	0.9~3.0	4.8	40
152	6"	167	0.3~1.0	0.9~3.0	7	40
203	8"	218	0.3~1.0	0.9~3.0	10	20



SUCTION AND DISCHARGER ACID-ALKALI HOSE

Tube: black, smooth, epr rubber compound

Reinforcement: high strength synthetic cord plus helix wire.

Cover:black, smooth (wrapped finish) epr rubber compound

Application:designed to handle a wide range of chemicals, acids and alcohols during Production and transport operations; it is specially recommended for the trasfer of industrial waters, Sea water and for use on water purification works

Temp Range: -40°C to 120°C

I.D		O.D	W.P.	B.P.	WEIGHT	LENGTH MAX.
MM	INCHI	MM	MPA	MPA	KG/M	M/ROLL
51	2"	61	0.3~1.0	0.9~3.0	1.4	60
64	2.1/2"	74	0.3~1.0	0.9~3.0	1.8	60
76	3"	87	0.3~1.0	0.9~3.0	2.1	60
90	3.1/2"	102	0.3~1.0	0.9~3.0	3	60
102	4"	115	0.3~1.0	0.9~3.0	3.7	60
127	5"	141	0.3~1.0	0.9~3.0	4.8	20
152	6"	167	0.3~1.0	0.9~3.0	7	20
203	8"	218	0.3~1.0	0.9~3.0	10	20



CEMENT SUCTION HOSE

Tube: black, smooth, compounded for long wear resistance in handing hard, sharp abrasive materials such as sand, gravel, shells, stones, etc.

Reinforcement: high strength synthetic cord plus helix wire

Cover:black, corrugated (wrapped finish) synthetic rubber highly resistant to weather, sea-water and abrasion

Application:Dry material suction and delivery hose specially designed for transfer of dry cement, sand gravel, feed, seeds, etc. by suction, gravity or by pneumatic systems.

Temp Range:-40°C to 85°C"

I.D		O.D	W.P.	B.P.	WEIGHT	LENGTH MAX.
MM	INCHI	MM	MPA	MPA	KG/M	M/ROLL
51	2"	63	10	30	1.72	60
64	2.1/2"	77	10	30	2.37	60
76	3"	91	10	30	3.86	60
102	4"	120	10	30	4.33	60
127	5"	148	10	30	7.23	60
152	6"	175	10	30	10.18	40



PVC SPIRAL STEEL WIRE REINFORCED HOSE

APPLICATIONS:The hose is widely used for drawing and conveying water, oil and powder in factories, agriculture, engineering, foodstuffs and sanitation lines.

CHARACTERISTICS: This hose with steel wire screwing inlaid in the hose is light, transparent, with small bending radius. It has good adaptability to hard weather conditions and minus pressure. With colorful symbol lines on the surface of the hose, it can be more beautiful.

Temp Range:-5℃~65℃

Other typePVC Steel Wire Reinforced Hose For Food-Stuff

PVC High Temperature Steel Wirereinforced hose

PVC Low Temperature Steel Wire Reinforced Hose

PVC Anti-Static Steel Wire Reinforced Hose

1.D.		O.D.	Length	W.P.	B.P.	Weight	packing size		Volume
inch	mm	mm	m/roll	MPa	MPa	kg/m	dia.	High	m3
3/4"	20	24.6±0.2	50	0.5	1.5	0.25	650	180	0.076
	20	25.4±0.2	50	0.5	1.5	0.3	650	180	0.076
1"	25	29±0.2	50	0.5	1.5	0.25	650	200	0.085
	25	29.4±0.2	50	0.5	1.5	0.3	650	200	0.085
	25	31.6±0.2	50	0.5	1.5	0.4	650	210	0.089
	25	31.8±0.2	50	0.5	1.5	0.5	650	210	0.089
1.1/4"	32	36.6 ±0.2	50	0.5	1.5	0.4	750	220	0.129
	32	37±0.2	50	0.5	1.5	0.5	750	230	0.129
	32	40.2±0.2	50	0.4	1.1	0.65	750	260	0.166
1.1/2"	38	42±0.2	50	0.4	1.1	0.4	850	310	0.224
	38	42.8±0.2	50	0.4	1.1	0.5	850	310	0.224
	38	44.6±0.2	50	0.4	1.1	0.7	850	310	0.224
	38	46±0.2	50	0.4	1.1	0.9	850	320	0.231
1.3/4"	45	52.8±0.2	50	0.4	1.1	0.8	900	300	0.243
	45	53±0.2	50	0.4	1.1	1	950	300	0.271
1.7/8"	48	57.8±0.2	50	0.4	1.1	1.1	950	320	0.289
2"	50	56±0.2	50	0.4	1.1	0.7	980	320	0.307
	50	56.4±0.2	50	0.4	1.1	0.8	980	320	0.307
	50	56.8±0.2	50	0.4	1.1	0.9	980	320	0.307
	50	57±0.2	50	0.4	1.1	1	980	320	0.307
	50	58±0.2	50	0.4	1.1	1.1	1000	310	0.31
	50	59.6±0.2	50	0.4	1.1	1.2	1000	310	0.31
2.1/2"	64	70±0.2	30	0.4	1.1	1.2	1050	300	0.331
	64	72.4±0.2	30	0.4	1.1	1.4	1050	300	0.331
	64	73.5±0.2	30	0.4	1.1	1.6	1050	300	0.331
	64	74±0.2	30	0.4	1.1	1.8	1050	300	0.331
3"	75	81.8±0.2	30	0.3	0.8	1.4	1050	340	0.375
	75	82.4±0.2	30	0.3	0.8	1.6	1050	340	0.375
	75	83.6±0.2	30	0.3	0.8	1.8	1050	340	0.375
	75	85±0.2	30	0.3	0.8	2	1130	330	0.421
	75	85.8±0.2	30	0.3	0.8	2.2	1150	350	0.463
3.1/2"	89	100±0.2	30	0.3	0.8	2.5	1250	350	0.547
4"	102	110±0.2	30	0.3	0.8	2.5	1250	450	0.703
	102	110.8±0.2	30	0.3	0.8	2.7	1180	430	0.599
	102	112±0.2	30	0.3	0.8	3	1180	430	0.599
	102	114.2±0.2	30	0.3	0.8	3.5	1180	440	0.613
	102	114.6±0.2	30	0.3	0.8	4	1180	450	0.627
	102	121.6±0.2	30	0.3	0.8	5	1180	460	0.641
	108	118±0.2	30	0.3	0.8	3.2	1180	470	0.615
	108	120±0.2	30	0.3	0.8	3.5	1180	480	0.616
5"	127	141±0.2	20	0.2	0.6	5	1440	430	0.892
6"	152	166±0.2	20	0.2	0.6	6.5	1700	430	1.243



PVC FIBER REINFORCED HOSE

APPLICATIONS: The product is used for conveying water, oil, gas under normal working condition in the factory, farm, ship, building and family.

CHARACTERISTICS: It is flexible, transparent, durable, non-toxic, without order, anti-erosion and adaptable to high pressure condition. By adding colorful symbol lines on the surface of the hose, it looks more beautiful.

Temp Range: -5℃~65℃

1.D.		0.D.	Length	W.P.	B.P.	Weight	Volume
inch	mm	mm	m/roll	MPa	MPa	kg/m	m3
1/5"	5	9	168	0.9	3	10	0.024
1/4"	6	9	180	0.8	2.5	10	0.024
	6	10	147	0.9	2.7	10	0.024
	6	11	111	1	3	10	0.024
5/16"	6	12	87	1.2	3	10	0.024
	8	11.4	143	0.7	2.4	10	0.029
	8	12	118	0.9	2.4	10	0.027
	8	13	90	1	3	10	0.253
3/8"	8	14	71	1.2	3.2	10	0.027
	9	13	107	0.7	2.7	10	0.026
	9	14	82	0.8	3	10	0.026
	10	13.6	110	0.6	2.4	10	0.026
	10	14	98	0.7	2.4	10	0.03
1/2"	10	15	75	0.8	2.5	10	0.028
	10	16	60	0.9	2.8	10	0.028
	12	16	168	0.6	2	20	0.064
	12	17	130	0.7	2.1	20	0.064
	12	17.5	116	0.8	2.4	20	0.064
	12	18	105	0.9	2.7	20	0.064
	13	17	157	0.5	1.5	20	0.064
35/64"	13	18	122	0.6	1.8	20	0.064
	13	19	98	0.7	2.1	20	0.064
	14	19	114	0.5	1.5	20	0.061
	14	20	92	0.6	1.6	20	0.061
5/8"	15	19.4	125	0.6	1.6	20	0.061
	15	20	107	0.7	1.6	20	0.061
3/4"	15	21	87	0.8	1.7	20	0.068
	16	20	130	0.6	1.4	20	0.068
	16	21	102	0.7	1.8	20	0.068
	16	22	83	0.5	1.6	20	0.068
	18	24	75	0.5	1.4	20	0.093
1"	19	23	112	0.6	1.4	20	0.093
	19	24	87	0.6	1.6	20	0.093
	19	25	71	0.6	1.5	20	0.093
	19	26	60	0.6	1.5	20	0.093
	20	25	83	0.5	1	20	0.093
	20	26	68	0.5	1	20	0.093
	20	27	57	0.5	1	20	0.093
1.1/4"	22	30	45	0.5	1	20	0.093
	25	30	68	0.5	1.2	20	0.093
	25	31	56	0.5	1.2	20	0.093
	25	32	47	0.5	1.2	20	0.093
1.1/2"	32	39	57	0.5	1.2	30	0.136
	32	40	49	0.5	1.2	30	0.136
	32	41	43	0.5	1.2	30	0.136
1.3/4"	38	45	48	0.5	1.2	30	0.134
	38	46	42	0.5	1.2	30	0.134
	38	47	37	0.5	1.2	30	0.134
2"	45	55	47	0.4	1.1	50	0.194
	50	60	42	0.4	1.1	50	0.23
2"	50	62	35	0.4	1.1	50	0.23



PVC TRANSPARENT TUBE

APPLICATIONS: The product is used for conveying water, oil, gas under normal working condition in the factories, farm, ship, building and family.

CHARACTERISTICS: It is flexible, non-toxic, without odor, and resistant to high pressure and erosion. By adding colorful symbol lines on the surface of the hose, it looks more beautiful.

Temp Range: -5°C ~ 65°C

I.D		O.D	Length	W.P.	B.P.	Weight	Bend Radius	Measure D x H
mm	mm	mm	m/roll	bar	bar	kg/roll	mm	mm
1/8"	3	4.8	200	2	6	2.8	20	400 x 110
5/32"	4	5.8	150		5	3.6	30	380 x 110
3/16"	5	7		100		1.5	3.6	35
1/4"	6	8	2.7		45		380 x 110	
5/16"	8	10	3.5		60		400 x 110	
3/8"	10	12	4.5		75		420 x 110	
1/2"	12	15	50	1	3	4	90	420 x 120
5/8"	15	18				5	115	420 x 130
3/4"	19	22				6.3	140	560 x 150
1"	25	30				14	180	660 x 160
1.1/4"	32	38	40	1	2.5	17	300	650 x 160
1.1/2"	38	44				20	350	780 x 200
2"	50	58				35	430	950 x 250



PVC GARDEN HOSE

APPLICATIONS: Being widely used for irrigation and washing in the parks, community, factories and families.

CHARACTERISTICS: Colorful, light, flexible, elastic, portable and with excellent adaptability.

Temp Range: -5°C ~ 65°C

I.D		THICKNESS	LENGTH	W.P. MPA	B.P. MPA	Volume	WEIGHT
inch	mm	mm	m	At 23°C		m3	KGS
3/8"	10	2	100	0.8	2.4	0.0159	10.2
1/2"	12	2	100	0.6	1.8	0.045	11.5
	12	2.5	100	0.7	2.1	0.048	14.8
	13	2	100	0.6	1.8	0.048	12.5
	13	2.5	100	0.7	2.1	0.052	15.8
5/8"	16	2	50	0.6	1.8	0.035	7.5
	16	2.5	50	0.5	1.5	0.038	9.5
3/4"	19	2.5	50	0.5	1.5	0.045	11
	19	3	50	0.6	1.8	0.048	13.5
1"	25	2.5	50	0.4	1.2	0.093	14
	25	3	50	0.4	1.2	0.093	17.1



PVC LAYFLAT HOSE

APPLICATIONS:It is an ideal product used for drainage in the fields of agriculture irrigation, forestry sprinkler irrigation, construction project, industrial and mining enterprise.

CHARACTERISTICS:Choosing high strength polyester filament and high quality PVC, it is successively winded, parted the threads regularly and molded by plastic coated once. With an attractive appearance, soft surface and light weight, high burst pressure and long service life, the product is acid & alkali resistant, aging resistant, stretching resistant, anti-wrinkle, non-toxic, flavorless and environmental protection.

Temp Range:-5℃~65℃

I.D		O.D	LENGTH	W.P. MPA	B.P. MPA	Volume	WEIGHT
inch	mm	mm	m	At 23℃		m3	KG/roll
1"	25	27.4	100	8	25	0.017	15
1.1/4"	32	34.4	100	8	25	0.02	17
1.1/2"	38	40.4	100	8	25	0.024	20
2"	51	53.2	100	5	15	0.034	25
	51	53.4	100	7	20	0.034	28
2.1/2"	64	66.2	100	5	14	0.046	30
	64	66.6	100	5	16	0.046	38
3"	76	77.4	100	3	9	0.06	40
	76	78.8	100	3	11	0.06	46
	76	79.6	100	3	30	0.06	60
4"	102	104.8	100	10	11	0.083	62
5"	125	127.8	100	3	11	0.109	75
6"	152	154.6	100	3	11	0.141	90



PVC GAS HOSE(LPG HOSE)

APPLICATIONS: Being used for conveying gas and liquid under low pressure, specially suitable for LPG in family.

CHARACTERISTICS: Being made from good quality PVC and rubber compound, the hose is flexible, elastic, safe and easy to seal.

WORKING TEMPERATURE: -5℃-65℃

I.D.		O.D	Length	W.P.	B.P.	Weight	Measure
Inch	mm	mm	m/roll	bar	bar	kg/roll	D x H mm
3/8"	9	14	100	2	6	18	500 x 160
	10	15				18.2	500 x 160
1/2"	13	20				24	600 x 170



PVC AIR HOSE

APPLICATIONS: The hose is widely used in pneumatic tools, pneumatic washing apparatus, compressors, engine components, machine service and civil engineering equipments.

CHARACTERISTICS: Being made of tough PVC materials and high tensile polyester reinforcement, this hose can work under very high working pressure. It is light, flexible, durable, anti-erosion, and explosion resistant.

WORKING TEMPERATURE: -5°C-65°C

I.D.		O.D.	Length	W.P.	B.P.	Weight	Measure
Inch	mm	mm	m/roll	bar	bar	kg/roll	D x H mm
1/4"	6.5	12	100	20	60	11	400x150
5/16"	8.5	14	100	20	60	13	420x150
3/8"	10	16	100	20	60	16.5	520x150
1/2"	13	20	100	20	60	12	440x150
5/8"	16	25	50	20	60	19.5	500x160
3/4"	19	28.5	50	20	55	24	560x180
1"	25	34.5	50	15	45	30	600x260
1.1/4"	32	44	50	15	45	48	800x260
1.1/2"	38	50	50	15	45	56	950x300
2"	50	64	50	10	30	84	1100x310



PVC Helix Suction Hose

Applications: Good substitute for rubber and metal hose in most application; Agriculture irrigation, chemical transfer, water, oil, grain and powder conveying.

Characteristics: Being light in weight, with good resistance to the hard weather conditions and minus pressure, and small bending radius. Excellent resistance to pressure, external impacts, chemical, gases, light acids and saline water.

WORKING TEMPERATURE: -5°C-65°C

I.D.		THICKNES S	Weight	THICKNES S	Weight	THICKNES S	Weight	THICKNESS	Weight
Inch	mm	mm	kg/m	mm	kg/m	mm	kg/m	mm	kg/m
3/4"	19	2	0.18	2.5	0.23	3	0.28	3.5	0.32
1"	25	2	0.23	2.5	0.29	3	0.35	3.5	0.41
1.1/4"	32	2.5	0.38	3	0.45	3.5	0.53	4	0.6
1.1/2"	38	2.5	0.44	3	0.53	3.5	0.63	4	0.72
2"	50	3	0.7	3.5	0.82	4	0.95	4.5	1.1
2.1/2"	63	3	0.88	3.5	1.04	4	1.19	4.5	1.38
3"	75	3.5	1.2	4	1.38	4.5	1.56	5	1.8
3.1/2"	88	3.5	1.4	4	1.62	4.5	1.83	5	2.2
4"	100	4	1.59	4.5	1.84	5	2.08	5.5	2.5
5"	125	4.5	2.59	5	2.88	5.5	3.18	6	3.5
6"	150	5	3.5	6	4.1	7	4.79	8	5.5
8"	200	6	5.1	7	5.9	8	6.8	9	7.58